

Product Information:

"A" cable suspension bolts are supplied with two square nuts. One nut is used to fasten the square head bolt to the pole and the other nut is used to secure a straight or angle cable suspension clamp to the bolt.



Material

Steel hot dip galvanized

5/8" Diameter - Minimum Tensile Strength 13,550

Catalog number	Bolt Length (in)	Thread Length (in)	Weight /100 (lbs)
LR6645.A01	8	4	85
LR6645.A02	10	6	104
LR6645.A03	12	6	120
LR6645.A04	14	6	138
LR6645.A05	16	6	153
LR6645.A06	18	6	168
LR6645.A07	20	6	183
LR6645.A08	22	6	198
LR6645.A09	24	6	214

3/4" Diameter - Minimum Tensile Strength 20,050

Catalog number	Bolt Length (in)	Thread Length (in)	Weight /100 (lbs)
LR6645.A10	10	6	165
LR6645.A11	12	6	187
LR6645.A12	14	6	204
LR6645.A13	16	6	220
LR6645.A14	18	6	220

Brace bolts

Product Information:

Brace bolts are used in place of carriage bolts or machine bolts to fasten braces to crossarms. The integral washer/hex head construction provides a static-proof



design.

Material

Steel hot dip galvanized

Minimum Tensile Strength 4,250 lbs

Catalog number	Size (in)	Thread Length (in)	Weight /100 (lbs)
LR8624- 1/2	3/8x4 1/2	2	21