

Description

The complete range of Earth Tapes manufactured from high conductivity tinned copper by Qingzhou in an extensive range of widths and thicknesses from 12.5 x 1.5mm (18.75sqmm C.S.A. Cross Section Area) to 50 x 8mm (400sqmm C.S.A.) .

Bare copper tape earth conductors with fault current ratings according to BS7430 with an initial copper conductor temperature of 30°C and a maximum temperature of 250°C.

Application

Bare copper earth tapes is used for earthing, bonding and protection of LV HV substations and networks.

Packing

Standard Wooden Case

Our Advantage

1. Factory direct sale, discount price, short delivery time
2. We provide one-stop professional packaging solutions
3. Complete quality inspection and certification
4. Help customers realize new profit resources and cost savings

Technical Information

AN Wallis Part Number	Earth Tape W x H	Copper Cross Sectional Area (CSA) / Thickness	Weight Per Metre	Standard Coil Size	Copper
TC 121	12.5mmx 1.5mm	18.75sqmm	0.17kg	100m	
TC 123	12.5mm x 3mm	37.50sqmm	0.33kg	100m	
TC 201	20mm x 1.5mm	30sqmm	0.27kg	100m	
TC 203	20mm x 3mm	60sqmm	0.53kg	100m	
TC 251	25mm x 1.5mm	37.5sqmm	0.33kg	100m	
TC 253	25mm x 3mm	75sqmm	0.67kg	25m & 50m	
TC 254	25mm x 4mm	100sqmm	0.89kg	50m	
TC 256	25mm x 6mm	150sqmm	1.33kg	40m	
TC 302	30mm x 2mm	60sqmm	0.53kg	50m	
TC 303	30mm x 3mm	90sqmm	0.80kg	50m	
TC 304	30mm x 4mm	120sqmm	1.07kg	40m	
TC 305	30mm x 5mm	150sqmm	1.33kg	40m	
TC 313	31mm x 3mm	93sqmm	0.83kg	50m	
TC 3154	31.5mm x 4mm	126sqmm	1.13kg	40m	
TC 316	31mm x 6mm	186sqmm	1.65kg	30m	
TC 383	38mm x 3mm	114sqmm	1.01kg	50m	
TC 385	38mm x 5mm	190sqmm	1.69kg	30m	

TC 386	38mm x 6mm	228sqmm	2.02kg	25m
TC 403	40mm x 3mm	120sqmm	1.06kg	40m
TC 404	40mm x 4mm	160sqmm	1.42kg	30m
TC 405	40mm x 5mm	200sqmm	1.78kg	25m
TC 406	40mm x 6mm	240sqmm	2.16kg	25m
TC 4063	40mm x 6.3mm	252sqmm	2.24kg	25m
TC 503	50mm x 3mm	150sqmm	1.33kg	40m
TC 504	50mm x 4mm	200sqmm	1.78kg	30m
TC 505	50mm x 5mm	250sqmm	2.22kg	20m
TC 506	50mm x 6mm	300sqmm	2.68kg	10m & 20m
TC 5063	50mm x 6.3mm	315sqmm	2.80kg	20m
TC 508	50mm x 8mm	400sqmm	3.60kg	15m