

Description

Copper/Tinned Soft Stranded Wire is a soft connecting line for electrical equipment for transmission (such as transformers, electric furnaces), electronic and electrical equipment, and thyristor components. It can also be used as an electrical grounding wire for electrical work.

Copper Soft Stranded Wire is supported by high quality round copper wire or tinned soft round copper wire. Through the toughening process during the processing, the finished product is soft, the appearance is neat and beautiful.

Technical Information

Material	Pure copper or tinned copper
Size	Custom Made
Customized	OEM or ODM mode service
Certification	ISO9001

Product Size

Product specifications	Area (mm ²)	Size(mm)	Outer Dia (mm)	Weight (kg/km)
TJR (X) -3/2.5	2.6	7×21/0.15	2.2	25
TJR (X) -3/4	3.96	7×32/0.15	3.2	38
TJR (X) -3/6	6.31	7×51/0.15	3.7	61
TJR (X) -3/8	7.67	7×62/0.15	4.1	74
TJR (X) -3/10	10.01	7×81/0.15	4.5	95
TJR (X) -3/12	12.09	12×57/0.15	5	115
TJR (X) -3/16	15.95	7×3×43/0.15	6.5	152
TJR (X) -3/20	20.4	7×3×55/0.15	7.8	195
TJR (X) -3/25	24.85	7×3×67/0.15	8.5	237
TJR (X) -3/35	34.87	7×3×94/0.15	9.8	332
TJR (X) -3/50	50.34	19×3×50/0.15	12	479
TJR (X) -3/70	70.47	19×3×70/0.15	15	670
TJR (X) -3/95	94.64	19×3×94/0.15	16.5	900
TJR (X) -3/100	100.2	18×3×105/0.15	18	952
TJR (X) -3/105	105.76	19×3×105/0.15	18.5	1005
TJR (X) -3/110	111.33	20×3×105/0.15	19	1058
TJR (X) -3/115	116.9	21×3×105/0.15	19.5	1111
TJR (X) -3/120	117.46	19×5×70/0.15	20	1117
TJR (X) -3/160	159.49	19×19×25/0.15	22	1517
TJR (X) -3/185	185	19×19×29/0.15	23	1760

TJR (X) -3/200	196.15	37×12×25/0.15	26	1866
TJR (X) -3/250	251.08	37×12×32/0.15	29	2388
TJR (X) -3/315	310.58	37×19×25/0.15	31	2954
TJR (X) -3/400	397.54	37×19×32/0.15	34	3782
TJR (X) -3/500	496.92	37×19×40/0.15	38	4727

Above is the common size, we also can do according to your requests. Please contact us to get to know more information about our products and service.