

Product Information:

Double arming bolts are fully threaded and used in double crossarm construction to secure and lock in spacing between crossarms.



Features

- Fully threaded and assembled with 4 square nuts
- Ends can accept eyenuts for deadend applications
- Length dimensions do not include points

7/8" Diameter - Minimum Tensile Strength 27,700 lbs

Catalog number	Bolt Length (in)	Weight /100 (lbs)
LR9112	12	283
LR9114	14	312
LR9116	16	341
LR9118	18	370
LR9120	22	399
LR9122	24	427
LR9124	26	456
LR9126	30	485
LR9128	32	514

LR9130	34	543
LR9132	36	572
LR9134	38	601
LR9136	40	630
LR9138	42	659
LR9140	12	688
LR9142	14	717

Material

Steel hot dip galvanized

5/8" Diameter - Minimum Tensile Strength 13,550 lbs

Catalog number	Bolt Length (in)	Weight /100 (lbs)
LR8860	10	118
LR8862	12	136
LR8864	14	142
LR8866	16	158
LR8868	18	187
LR8870	20	192
LR8872	22	208
LR8874	24	224
LR8876	26	240
LR8877	28	256
LR8878	30	264

LR8879	32	284
LR8880	34	295
LR8881	36	332

3/4" Diameter - Minimum Tensile Strength 20,050 lbs

Catalog number	Bolt Length (in)	Weight /100 (lbs)
LR8883	10	163
LR8882	12	196
LR8884	14	220
LR8886	16	240
LR8888	18	260
LR8890	20	284
LR8892	22	304
LR8894	24	336
LR8896	26	345
LR8897	28	365
LR8898	30	386
LR8899	32	400
LR9003	34	420
LR9004	36	460