

Features

- Square head and square nut

Roll threaded

- Bolts 1/2”diameter and larger and 7”length and longer also have cone points which permit driving without damage to Threads



5/8”Diameter - Minimum Tensile Strength 13,550 lbs

Catalog number	Bolt Length (in)	Weight /100 (lbs)
J8801-1/2	1 1/2	30
J8802	2	34
J8802- -1/2	2 1/2	38
J8803	3	44
J8804	4	50
J8805	5	57
J8806	6	62
J8807	7	72
J8808	8	82
J8809	9	88
J8810	10	94
J8812	12	108
J8814	14	125
J8816	16	136
J8818	18	152
J8820	20	170
J88022	22	184
J88024	24	200
J88026	26	224
J88028	28	242

Material

Steel hot dip galvanized

3/8”Diameter - Minimum Tensile Strength 4,250 lbs

Catalog number	Bolt Length (in)	Thread Length (in)	Weight /100 (lbs)
LR8604	3	3	13

LR8604	4	3	15
LR8604-1/2	4 1/2	3	17
LR8605	5	3	18
LR8606	6	4	21
LR8608	8	4	27

1/2" Diameter - Minimum Tensile Strength 8, 500 lbs

Catalog number	Bolt Length (in)	Weight /100 (lbs)
LR8701-1/2	11/2	18
L R8702	2	20
LR8702- 1/2	2 1/2	23
LR8703	3	25
L R8704	4	31
L R8705	6	36
L R8706	7	48
LR8707	9	50
LR8708	10	57
L R8709	12	60
LR8710	14	70
LR8712	16	79
LR8714	11 1/2	89
LR8716	2	18