

Product Description

Pure Copper Earth Conductor is used as flexible connector in electric transmission and distribution appliance (such as volt transformer, electric stove), electronic equipment and thyristor. Non-Insulated Stranded Conductor also could be used for earthing system of power plant ,transformer station ,tower ,communication station ,airport, railway, subway station , high building ,computer room ,petro plant ,oil reservoir in the environmental of moist ,saline and alkaline ,acid and chemical corrosion medium environmental.Wire in electric working.

Material	99.9%pure copper
Diameter	10-500 mm ²
Life	≥50 years
Tensile Strength	≥396 mpa
Characters	Easy installation ,Good conductivity
Available service mode	OEM,ODM
Certificate	ISO9001:2015

Regular Products size(We Accept Customization)

Negotiable price According to different material/size and Purchase quantity

Product specifications	Nos/Dia	Outer Dia	Weight
	(pcs/mm)	(mm)	(kg/km)
TJ-10	7/1.35	4.05	90.8
TJ-16	7/1.70	5.1	145
TJ-25	7/2.14	6.42	229
TJ-35	7/2.52	7.56	317
TJ-50	19/1.78	8.9	429
TJ-70	19/2.14	10.7	620
TJ-95	19/2.52	12.6	860
TJ-120	37/2.03	14.21	1086
TJ-150	37/2.25	15.75	1334
TJ-185	37/2.52	17.64	1673
TJ-240	61/2.25	20.25	2199
TJ-300	61/2.52	22.68	2759
TJ-400	61/2.85	25.65	3528
TJ-500	61/3.20	28.8	4448