

## Overview

Standard glass disc insulator products are composed of iron caps, power tempered glass parts and steel feet, and are glued together with cement glue. This product all adopts the international advanced cylindrical head structure, which is characterized by small head size, light weight, high strength and large creepage distance. It can save metal materials and reduce the line cost. In order to meet the needs of live working, the domestic traditional structural shape is adopted on the brim.

## Parameter

General code	LXY Series	FC Series	LXP Series	Nominal diameter	Structure height H(mm)	Net weight of single piece
				D(mm)		(kg)
U70BL	LXY1-70	FC70/146	LXP-70	255	146	3.78
U70BS	LXY-70	FC70/127	LXP2-70	255	127	3.77
U100BL	LXY-100	FC100/146	LXP-100	255	146	4.1
U100BS		FC100/127	LXP2-100	255	127	3.9
U120BL	LXY-120	FC120/146	LXP-120	255	146	4.2
U120BS		FC120/127	LXP2-120	255	127	3.9
U160BL		FC160/170	LXP-160	280	170	6.5
U160B	LXY3-160	FC160/155	LXP3-160	280	155	6.2
U160BS		FC160/146	LXP4-160	280	146	6
U210B	LXY3-210	FC210/170	LXP-210	280	170	6.7
	LXY-240					6.8
	LXY3-300					10.7