


Overview

suspension clamps are designed to hang LV-ABC lines with insulated neutral messengers. The neutral messenger is fixed by an adjustable grip device. A movable link allows longitudinal and transversal movement of the clamp body.

Standard suspension clamp version ES is supplied with preinstalled bracket. The upper bulge of the bracket prevents the clamp from turning over the bracket.

Suspension Clamps are also available without bracket and with a fuse link. These suspension clamps are fixed to a pole with a pig tail hook or bracket.

- Toolfree installation
- No loosable parts
- Suspension Clamp and link made of polymer giving an additional insulation between the cable and the pole.
- Exceeds requirements according to NF C 33 040, EN50483
- Suspension Clamp and movable link made of weather and UV resistant glass fibre reinforced polymer
- Universal fixing of bracket by 1 bolt M16 or stainless steel strap of 20x0,7 mm.
- Bracket made of corrosion resistant



Model	Conductor Range (mm ²)
UNI94	16-95
UNI95	16-95
1.1A	16-95
1.1B	16-95
ES54-14	16-95
PS1500	16-95
SHC-1	4×(16-35)
SHC-2	4×(50-120)
SHC-3	4×(50-70)
SHC-4	4×(50-70)
SHC-5	4×(70-95)
SHC-6	4×(70-95)